

Presented by:

Troy M. Green, PE **Executive Vice President** J-U-B ENGINEERS, Inc. 2810 W. Clearwater Avenue Kennewick, WA 99337 (509)783-2144 tmg@jub.com











Typical Scrape Manure











Typical Flush Manure












TIREPower AD Development Goals

- AD Solution for Dilute Flow Streams
 Especially Flush Dairy Operations
- Shorten Hydraulic Retention Time
- Media Capable of Treating Manures without Plugging
- More Affordable AD System











Retained Solids From Pilot
















Fixed Film Image From Pilot













Media Profile From Pilot











Pilot Summary

- Operated 1 Year Sept 2005 to Sept 2006
- Total Volatile Solids and COD Removals Between 30% and 45% at 7 Days HRT
- No Indications of Media Plugging with Sand Laden Dairy Manure
- Advanced Model Developed
- Study Warranted Full Scale Prototype to Optimize Design and Demonstrate Capabilities







TIREPower AD – Threemile

- Commercial Scale Digester Facility
- Partners Bonneville Environmental Foundation, NW Natural Gas, and Threemile Canyon Farms, LLC
- 12-18 Month Demonstration/Test Phase
- \$1.5 Million Budget:
 - Phase 1 Digester Construction and Testing
 - Phase 2 Full Operation with Biogas Put To **Beneficial Use**









TIREPower Digester Basin













Digester Full of Tire Media















Completed HDPE Digester Cover













Pump Station & Effluent Weir













Heat Exchanger and Boiler Container













Boiler Container














Biogas Blower Building













Biogas Flaring 10-Days After Startup














Threemile Operations Plan

- Start-Up Phase Began January 18, 2010
 - Burnable Biogas within 10 Days
 - 60% Methane Content within 20 Days
 - Converted Boiler to Burn Biogas March 24, 2010
- HRT Optimization Phase Completed
 September 2010 (6.5 to 7.5 Day HRT)
- 6 Month Performance Evaluation Phase Currently Underway
- Process Optimization Phase Spring 2011





Influent and Effluent Imhoff Cone Data



····· Influent Imhoff Cone

..... Effluent Imhoff Cone Data

----25 per. Mov. Avg. (Influent Imhoff Cone)


-25 per. Mov. Avg. (Effluent Imhoff Cone Data)


















Influent Total and Volatile Solids










Total Biogas Produced at 7 Day HRT










Biogas Quality (% Methane)










Robust Recovery of Digester Performance











TIREPower Advantages

- Feasible for Dilute Flow Streams
- Applicable to Scrape Dairy Operations or Thicker Organic Flow Streams
- Short Hydraulic Retention Time Means Smaller Digester Vessel
- Media Capable of Retaining Biomass for Enhanced Treatment without Plugging
- Reproducible / Modular
- Retained Biomass/Bacteria Resist Upsets
- More Affordable AD System









Thanks to Our Partners

- Bonneville Environmental Foundation
- Northwest Natural Gas
- Threemile Canyon Farms, LLC
- WSU Biological Systems Engineering Department
- Miller Mechanical Specialties, Inc. Biogas Handling
- Brown and Caldwell Engineering & Technical Support
- HiLine Engineering and Fabrication, Inc. Pump Station/Controls
- Apollo, Inc. General Contractor
- Phase 2 Electric Electrical Installation
- Cole Industrial, Inc. Boiler System
- Les Schwab Tire Centers Tire Supplier
- Vaughan Company, Inc. Chopper Pumps
- Komax Systems, Inc. Heat Exchangers





